



Features	
Model	Solid
Chipset	Conexant 11252
Data Protocol & Speed	ITU V.92 ITU V.90 & K56flex (up to 56 Kbps) ITU V.34 (33.6-24 Kbps) ITU V.32bis (14.4-4.8 Kbps) ITU V.32 (9.6-4.8 Kbps) ITU V.22bis (2.4-1.2 Kbps) ITU V.22 (1.2 Kbps) ITU V.23 (75/1200-600 bps) ITU V.21 (300 bps) Bell 212 ^a (1200 bps), Bell 103 (300 bps)
Fax Protocols	ITU-T V.17, ITU-T V.29, ITU-T V.27ter Group III, Class 1, 1.0
Fax Speed	300, 2400, 4800, 7200, 9600, 12000, 14400
Error Correction	ITU-T V.43, LAP-M, MNP2-4
Data Compression	ITU-T V.44, ITU-T V.42bis, MNP5
DTE Speed	300, 1200, 2400, 4800, 9600, 14400, 19200, 38400, 57600, 115200
Command Set	AT Command
System Compatibility	Windows 98, 2000, NT 4.0, ME, XP
Interface	PCI
Caller ID	US and Canada
Speakerphone	Software Speakerphone (Through Sound Card)
Telephone Answering machine	Yes (Through Sound Card)
Voice mode	Yes (Through Sound Card)
DTMF detection	Tone
Flow Control	XON/XOFF, CTS/RTS
Auto Answer	Yes
Plug and Play	Yes